

UNINTERRUPTIBLE POWER SYSTEMS



1000

1000 Series

700 VA to 3000 VA UPS

3 Year
Warranty

- True On-Line Double Conversion UPS
- Auto-Restart and Cold Start Features
- Programmable Load Shed Receptacles
- Intelligent Charger with Rapid Charge in Only 4 Hours to 90%
- Wide Input Voltage Window
- Wide Input Frequency Window for Complete Generator Compatibility
- Input Power Factor Greater than 0.97
- Output Power Factor 0.70
- LCD Display in Multiple Languages
- Optional Network Interface Card - RemotEye II®
- Optional Environmental Monitoring Device

1000 Series UPS

Tower	US 120 V Model	UT1A1A007C6	UT1A1A010C6	UT1A1A015C6	UT1A1A020C6	UT1A1A030C6
	International 230V Model	UT1E1E007C6	UT1E1E010C6	UT1E1E015C6	UT1E1E020C6	UT1E1E030C6
Rackmount (2U)	US 120 V Model	UT1A1A007C6RKB2	UT1A1A010C6RKB2	UT1A1A015C6RKB2	UT1A1A020C6RKB2	UT1A1A030C6RKB2
	International 230 V Model	UT1E1E007C6RKB2	UT1E1E010C6RKB2	UT1E1E015C6RKB2	UT1E1E020C6RKB2	UT1E1E030C6RKB2
Input	Voltage	120 VAC (80 to 144 V, +20% to -33%)				
	Voltage (International)	230 VAC (161 to 276 V, +20% to -30%)				
	Capacity (VA)	700 VA	1000 VA	1500 VA	2000 VA	3000 VA
	Capacity (W)	490 W	700 W	1050 W	1400 W	2100 W
	Frequency	50/60 Hz Auto-Sensing				
	Power Factor	Greater than 0.97				
	Topology	True On-Line, Double Conversion, Input PF Correction				
Output	Voltage	100/110/115/120/127 VAC				
	Voltage (International)	208/220/230/240 VAC				
	Frequency	50/60 Hz Auto-Sensing				
	Wave Form	Sine Wave, Zero Transfer Time				
	Load Power Factor	0.70				
	Efficiency AC/DC/AC	Greater than 86%				
	Rated Current	5.8 A	8.3 A	12.5 A	16.6 A	25 A
	Rated Current (International)	3.0 A	4.3 A	6.5 A	8.7 A	13 A
	Overload Capacity	125% for 1 Minute, 150% for 10 Seconds				
	Crest Factor	3.0 at Full Load				
Battery	Battery Type	Valve Regulated Lead Acid; Flame Retardant (7.2 AH)				
	DC Link (Tower & 2U)	24 V (Two 12 V Batteries)				
	Backup Time (Tower & 2U)	7 Minutes (Full Load)	7 Minutes (Full Load)	6 Minutes (Full Load)	7 Minutes (Full Load)	6 Minutes (Full Load)
	Interface	RS-232 and USB Standard, Remote Contact, RemotEye II® and EMD Option				
Physical	Dimensions of Tower (L x W x H)	16.5" x 6.0" x 9.4"			16.7" x 8.9" x 14.2"	
	Dimensions 2U (L x W x H)	16.7" x 16.9" x 3.5"			25.0" x 16.9" x 3.5"	
	Weight (Tower/2U)	31 Lbs/34 lbs	35.6 lbs/37.6 lbs	37.4 lbs/37.6 lbs	68.4 lbs/69.5 lbs	72.6 lbs/71.5 lbs
	Line Cord	5 to 15P			5 to 20P	L5 to 30P
	Line Cord (International)	IEC 320				
	Receptacles (Tower/2U)	NEMA 5 to 15 P (6/6)			NEMA 5 to 15 P (12/4)	
	Receptacles (Tower/2U) International	IEC 320 (4/4)			IEC 320 (8/8)	
Environment	Operating Temperature	0 to 40°C (32 to 104°F)				
	Altitude	11500 ft (3500 m) Above Sea Level				
Warranty		Three Years on Electronics				
		Two Years Full Replacement on Battery (See Toshiba warranty policy for full details.)				



1 to 1.5 kVA Tower



1 to 1.5 kVA Rackmount 2U



1 to 1.5 kVA Tower 230 V

UPS ADJUSTABLE SPEED DRIVES MOTORS CONTROLS INSTRUMENTATION PLC

TOSHIBA

Available Through:

**TOSHIBA INTERNATIONAL CORPORATION
INDUSTRIAL DIVISION**

13131 West Little York Road, Houston, Texas 77041
 Tel 713/466-0277 Fax 713/466-8773
 US 800/231-1412 Canada 800/872-2192 Mexico 01/800/527-1204
 www.toshiba.com/ind
 Copyright 12/2006



UPS1000SERIES061201